



Boost Your Viewing Experience

The Vivitek D862 is a high-performance digital projector that offers exceptional digital images with full color saturation. This projector features native XGA resolution, multiple connectivity options and 3000 ANSI Lumen of brightness. Add 3D-ready capabilities, and the D862 is the ideal projector for just about any multimedia/video applications. Great functionality, high performance and excellent value for money, all found in the Vivitek D862.

Features

- Native XGA (1024x768) resolution
- 3000 ANSI Lumens of brightness and a 5000:1 contrast
- DLP® and BrilliantColor™ technologies from Texas Instruments
- High-efficiency lamps that last up to 6000 hours (ECO mode)
- Sealed optical engine
- Top-loading for lamp easy replacement
- Connectivity options include: Two (2) HDMI v1.3, VGA-In, S-Video, Composite
- 3D-Ready via DLP Link™
- RS-232c for one-touch automation setup for simple screen/projector automation functionality

| Specifications | |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Brightness | 3000 ANSI Lumen |
| Native Resolution | XGA (1024 x 768) |
| Max. Resolution | UXGA (1600 x 1200) @60Hz |
| Contrast Ratio | 5000:1 (Full On/Off) |
| Lamp Life and Type | ≈6000/4500 Hours (Eco/ Normal Mode), 190W |
| Lamp Part # | 5811117175-SU |
| Display Type | Single 0.55" DLP® Technology by Texas Instruments |
| Throw Ratio | 1.6 to 1.92:1 (Distance/Width) |
| Image Size (Diagonal) | 25.6" to 308" / 0.6 to 7.6 m |
| Projection Distance | 1.0 to 10.0 m |
| Projection Lens | F=2.50-2.72, f=17.81-21.35mm |
| Zoom Ratio | 1.2:1 Manual Zoom/Focus |
| Aspect Ratio | 4:3 Native, 16:10 & 16:9 Compatible |
| Offset | 128% |
| Keystone Correction | ±15° Vertical |
| Color Spectrum | 1.07 Billion |
| Horizontal Scan Rate | 15, 30 to 90 KHz |
| Vertical Scan Rate | 43 to 85 Hz |
| Speaker | 10 Watt |
| Projection Method | Table Top or Ceiling Mount (Front or Rear) |
| Uniformity | 85% |
| Computer Compatibility | UXGA, SXGA+, SXGA, WXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible |
| Video Compatibility | SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) |
| I/O Connection Ports | SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L) |
| Security | Kensington® Lock Port |
| Weight | 2.7 kg |
| Dimensions (W x H x D) | 285 x 122 x 261 mm |
| Noise Level | 35dB/32dB (Normal/Eco Mode) |
| Power | Supply: AC 100-240V, 50/60Hz Consumption: 230W (Standard Mode), 260W (Boost Mode), < 0.5W (Standby Mode) |
| Warranty | 3 Years, 1 Year (or 1,000h) on the Lamp |
| Standard Accessories | AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Lens Cap, Warranty Card |
| Optional Accessories | Replacement Lamp, Remote |
| UPC | 814964335425 |

