

## NovoTouch EK757i

EDLA Certified, True 75" 4K-UHD interactive display with wireless collaboration and touch interaction



### Features:

#### Hardware

- 75" display with 4K Ultra-HD resolution for outstanding details and stunning visuals
- 3mm-thick toughened glass for added protection against scratches or screen damage
- Built-in Octa-core processors enhance computing capabilities for various user needs
- Front bezel USB-A, USB-C ports for quick connection to USB keyboards/mice, memory drives and data
- USB-C 65W will charge your USB-C laptop on the go
- High-speed Wi-Fi 6 connection
- Dual RJ45 ports for easy Ethernet expansion
- 2.1 channel speakers will deliver better audio quality than before.

#### Software

- Integrated with NovoConnect wireless presentation and collaborative system for cable-free and hassle-free presenting in the classroom
- Connect to 64 users simultaneously, and allow 4 people to present on one display to facilitate large group work
- Built-in whiteboard and Screen annotation Apps to facilitate efficient collaboration in meeting rooms and classrooms
- NLiveScreen & NLiveReceiver allows you to mirror the screen shown on one NovoTouch to other NovoTouch.
- Centralized device management through Remote Manager Cloud or Windows software, simplifying IT administration
- Built-in NovoDS capability as an all-in-one digital signage solution, easy to set up and manage via NovoDS.com Cloud service

### Specification:

Display	Type/Technology	Backlit D-LED (ADS Panel)		
	Panel Size	75"		
	Brightness (Typ.)	450cd/m2		
	Contrast Ratio (Typ.)	5,000:1		
	Native Resolution	4K Ultra-HD (3840 x 2160)		
	Viewing Angle (H/V)	178°/178°		
	Aspect Ratio	16:9		
	Response Time (MS)	6ms (Typ.)		
	Refresh Rate (Hz)	60Hz		
	Estimated Lifetime (Typ.)	50,000 hours (Min)		
	Display Color (Bit)	1.07 billion (10-bit)		
	Installation Orientation	Landscape		
	Daily Operation (Hours/Days)	16/7		
Interactivity	Technology	Infrared Touch		
	Touch Points	Writing	10 Point (Standard)	
		Touch	50 Point (Standard)	
	Accuracy	Finger	±1mm (Over 90% area)	
		Passive Pen	±1mm (Over 90% area)	
	Response Time	<3ms		
	Touch Resolution	32,768 x 32,768		
Surface Protection	3mm-Thick Toughened Glass			
Touch Tools	Finger, Stylus, Glove, Opaque Objects	Supported		
	Anti-Palm	Supported		
Operating System	System Version	Android™ v14.0		
	CPU	Multi-Core High-Performance ARM®CPU		
	GPU	Mali™ G52		
	RAM	16GB DDR5		
	Internal Storage	128GB (eMMC Flash)		
Connectivity	Input	Display	HDMI v2.0 x2 Side HDMI v2.0 x1 Front	
		Audio	Mic-In (3.5mm) x1	
	Output	Display	HDMI-Out v2.0 x1 (up to 4K@60Hz)	
		Audio	Line-Out (3.5mm) x1 SPDIF-Out x1	
	Internet	LAN (RJ45) x2 In/Out		
	Control	RS232-In x1		
	Wireless	WiFi	WiFi-6 IEEE802.11ax (2.4GHz/5GHz)	
		Bluetooth	BT 5.2	
		I/R Receiver	Front x1 (±25° Angle, >8m Distance)	
	USB-A	Front	USB 3.0 x2	
		Side	USB 3.0 x2, USB 2.0 x1	
	USB-B	Front	USB-B x1 (Touch Port for HDMI-In Front)	
		Side	USB-B x1 (Touch Port for HDM-in 1/2)	
	USB-C	Front	USB-C x1 (65W charging)	
		Side	USB-C x1 (Data Only)	
Expansion	Windows Module (Option)	Standard Intel 80pin OPS (Option)		
Audio	Speakers	18W*2 + 8W subwoofer*1		
	Power Supply (Internal)	AC 100 - 240V, 50/60Hz (4A)		
	Consumption	≤360W		
Power	Standby Mode	≤0.5W (Standby)		
	VESA Mounting (FPMPMI)	6 – M8 × 25mm, 800 x 400mm		
Physical Characteristics	Mini PC VESA Mount	100 x 100mm		
	Dimension (L x H x D)	1,705.7 x 90.2 x 1,032.3 mm		
	Weight	50.8kg		
	Color	Gray		
Accessories	Standard	AC Power Cord, Stylus (x2), Remote Control (W/Batteries), Wall Mount Kit, HDMI Cable (3M), Touch Cable (3M) Documentation Kit		
	Optional	LauncherPlus Windows OPS Module – Standard 80pin		

©2025 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.