



Mid to Large Meeting Room Laser Projector with Excellent ROI

- 0.67" DLP® and BrilliantColor™ technology
- High brightness with 30,000 hours of laser life (Eco mode)
- Powered Lens Control with Lens Positioning Memory (LPS)
- Low power consumption designed to reduce energy costs
- Large projection size with excellent picture quality
- Constant Brightness for extend light source life & easy blending
- IPX6 High standards dust protection to extend projector life
- 360° free installation and multiple geometric adjustments for easy installation
- Compatible with UHD-4K input signals
- Supports Art-Net for stage control
- "Rental Mode" ready for rental applications
- Built-in Speaker 10w x2
- HDBaseT™ interface for the transmission of high quality audio and video (4K) data over 100M
- Supported network & projector installation control software
- Available in nine (9) interchangeable motorized lens (Optional)



Corporate laser projector

A smart choice for mid to large corporate meeting rooms, the DU7099Z laser projector offers a low total cost of ownership and delivers tremendous value for companies. With maintenance-free durability for up to 20,000 hours, easy installation, and management, the DU7099Z is a reliable solution. It ensures superior visibility with 8,000 ANSI lumen brightness and true-to-life colors within the Rec. 709 color space, all while operating exceptionally quietly at 33dB. Engineered with advanced thermal technology to enhance performance and durability, this projector seamlessly blends an exceptional viewing experience with top-cost efficiency. Moreover, the DU7099Z can seamlessly integrate with Vivitek's NovoConnect Solution for wireless presentation and collaboration



DU7099Z

Display Type	Single chip DLP® Technology by Texas Instruments
Brightness	8000 ANSI Lumens
Native Resolution	WUXGA (1920 x 1200)
Max. Resolution	4K-UHD (3840 x 2160) @60Hz
Contrast Ratio	3,000,000:1 (Full On/Off)
Native Aspect Ratio	16:10
Keystone Correction	Vertical +/-30°; Horizontal +/-30°
Throw Ratio	9 optional lenses from 0.50:1 to 8.3 :1 throw ratio range
Zoom Ratio	Motorized
Offset	Motorized Lens Shift
Lens Shift Range	Vertical: Bottom 50% to Top 70%, Horizontal: Left 15% to Right 15%
Features	3D Ready(DLP link, PC+Video), Direct 3D (HDMI 1.4a), 3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L), 4K-UHD
I/O Connection Ports	VGA-In (15pin D-Sub), HDMI Number of Ports v.2.0 (x2), DVI-D, Component (5 BNC) (RGBHV) , Component (YPbPr BNC x 3), Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack), VGA-Out (15pin D-Sub), Audio-Out (RCA), RJ45 (x2: LANx1, HDBaseTx1), RS-232 (x2: In and Out), 3D-Sync (x2: In and Out), USB A (Power Only), USB B (Service), Remote Jack(wire remote)
Lamp Life and Type	Lamp free design. Laser light source lasts up to 20,000 hours
Speakers	10W x 2
Dimensions (W x D x H)	470 x 517 x 202mm
Noise Level	33dB/31dB (Normal/Eco. Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 465W (Normal Mode), <0.5W (Standby)
Control Software	Contrôle PJ V3.0.0.4
	Large Venue Laser Warranty, Standard Laser Phosphor Projector Warranty
	VGA Cable, Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Remote Control P/N (5042221900)
UPC Code	DU7099Z-WH: 813097024350; DU7099Z-BK: 813097024367

-	-	Short Throw (Z)	Normal Throw 1	Normal Throw 2	Standard Lens	Long Throw 1	Long Throw 2	Long Throw 3	Long Zoom 4
-	-	16:10	16:10	16:10	16:10	16:10	16:10	16:10	16:10
-	-	0.77 - 1.1	1.1 - 1.3	1.25 - 1.60: 1	1.54-1.93: 1	1.93-2.9	2.22-3.67:1	3.58-5.38:1	5.31-8.26:1
-	-	1-12	1-14,26	1.346-17,5	2-21,2	2.00-20.00	1.87-40.33	3.01-59.02	4.42-91.54
-	-	42.3-500	35.8-500	39.1-500	40-500	31.8m-500	40-500	40-500	40-500
-	-	1.42x	1.18x	1.28x	1.25x	1.50x	1.65x	1.5x	1.55x
-	-	2.1 - 2.6	2.05 - 2.27	2.0 - 2.44	2.02 - 2.40	2.5 - 3.1	1.86-2.48	1.85-2.41	1.85-2.48
-	-	11.45 - 16.32mm	16.64 - 19.54 mm	18.65 - 23.85 mm	22.84 - 28.61 mm	28.5 - 42.75mm	32.9 - 54.2 mm	52.8 - 79.1 mm	78.5 - 121.9 mm
-	-	SS-5811129741- VV (D86-0711)	SS-5811129742- VV (D86-1113)	SS-5811131167- VV (D86-1216)	SS-5811129740- VV (D86-1519)	SS-5811131168- VV(D86-1929)	3797745000- SVK (D88-SMLZ01)	3797745400- SVK (D88-LOZ101)	3797744900- SVK (D88-LOZ201)