



WUXGA Large Venue Projector

FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 6,200 ANSI lumens of brightness with single-lamp system
- WUXGA resolution for clear and crisp image
- HDBaseT for robustness with long signal transmission
- Wide lens shift range allows easy placement of the projector without distorting the image
- Image adjustment is made easy with 4 corner correction and keystone correction
- Easy projector monitor and control over network



High performance and easy installation features

The DU5671 offers a range of features that make it the ideal projector choice for the professional installation market. In addition to 6200 ANSI lumens of brightness, the WUXGA image resolution delivers excellent fidelity and large screen area for simultaneous display of video conferencing, presentations, and display of charts and graphs. With the installer in mind the DU5671 features horizontal and vertical lens shift as well as a centered lens for easy installation and maintenance. The projector has five interchangeable lens options for flexible positioning with regard to varying screen sizes or projection distance requirements and a comprehensive range of connectivity options.



DU5671

SPECIFICATIONS

Image	Display Type	Single chip DLP® Technology by Texas Instruments
	Brightness	6200 ANSI Lumens
	Native Resolution	WUXGA (1920 x 1200)
	Max. Supported Resolution	WUXGA (1920 x 1200) @60Hz
	Contrast Ratio	2,000:1
	Native Aspect Ratio	16:10
	Keystone Correction	Vertical +/-30°; Horizontal +/-25°
Optical	Image Size (Diagonal)	Depending on lens selection. See lens table below.
	Projection Distance	Depending on lens selection. See lens table below.
	Projection Lens	5 optional lenses from 0.78:1 to 3.00-5.01:1 throw ratio range
	Zoom Ratio	Depending on lens selection. Manual Zoom & Focus
	Offset	Manual Lens Shift
	Lens Shift Range	Vertical: +55%, -15%; Horizontal: +/-5%
Features	Features	3D Mandatory Formats supported (top/bottom, right/left, frame sequential)
Compatibility	Video	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Connectivity	I/O Connection Ports	VGA-In (15pin D-Sub) (x2), HDMI Number of Ports v.1.4b (x2), DVI-D, Component (5 BNC) (RGBHV) , S-Video, Composite Video, Audio-In (RCA) , Audio-In (Mini-Jack) (x2), VGA-Out (15pin D-Sub), Audio-Out (Mini-Jack), RJ45 (x2: HDBaseTx1, LANx1), 12v Trigger (3.5mm Mini-Jack), RS-232, 3D-Sync (Out), USB A (Power Only), USB B (Service), Remote Jack(wire remote)
General	Lamp Life and Type	1,500 / 2,000 Hours (Normal / Eco. Mode), 430W / 320W
	Speakers	3W
	Dimensions (W x D x H)	432 x 345 x 181mm
	Weight	8.8 kg
	Noise Level	43dB/38dB (Normal/Eco Mode)
	Power	Supply: AC 100-240V, 50/60Hz. Consumption: 410W (Eco Mode), 540W (Normal Mode), <0.5W (Standby)
	Warranty	Large Venue Warranty: 5 years projector / 1 year on lamp or 1.000 hours whichever comes first
	Standard Accessories	VGA Cable, User Manual (CD), Lens Cap, Quick Start Guide, Warranty Card (by region), Remote Controller (with battery), AC Power Cord
	Optional Accessories	Spare Lamp P/N (5811122169-SVV), 3D Glasses P/N (3534257700), Remote Control P/N (5041846600)
	UPC Code	813097023384

OPTIONAL LENSES

Lens Name	Short Throw	Standard Lens	Wide Fix	Long Zoom 1
Aspect Ratio	16:10	16:10	16:10	16:10
Throw Ratio	1.1-1.3:1	1.54 - 1.93:1	0.78:1	1.93 - 2.89:1
Projection Distance	1m-9m	1.5m-7m	0.5m-3m	2m-20m
Image Size	30-300	30-300	25-200	33-481
Zoom	1.18x	1.25x	1x	1.5x
F Number	2.05 - 2.27	2.46 - 2.56	2.5	2.5 - 3.1
Focal Length	16.64 - 19.54 mm	22.8 - 28.5 mm	11.46 mm	28.5 - 42.75 mm
Part Number	5811120054-SVV (LNS-5STZ)	5811119236-SVV (LNS-5SZ1)	5811120818-SVV (VL904G/LNS-5FX2)	5811119237-SVV (VL908G/LNS-5LZ1)