



## Large Venue Presentation Solution for Demanding Multimedia Applications

### FEATURES

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 6,500 ANSI lumens of brightness with dual-lamp system
- WUXGA resolution for clear and crisp image
- HDBaseT for robustness with long signal transmission
- Installation flexibility is ensured with 8 optional lenses from 0.38:1 to 5.31-8.26:1 throw ratio range
- Motorized and wide lens shift range allows easy placement of the projector without distorting the image
- Image adjustment is made easy with 4-corner and keystone corrections
- Easy projector monitor and control over network



## Professional projector for WUXGA high definition presentations

The Vivitek DU6771 is designed for large meeting room where brightness and installation flexibility is the key consideration. Featuring dual-lamp technology, interchangeable lenses and advanced display technologies the DU6771 delivers bright, superb digital images with full color saturation. Intended for the heavy duty applications it can operate 24/7, delivering high brightness of 6500 ANSI Lumens. The model features a high contrast ratio of 3000:1 for deep blacks and rich colours. The DU6771 is unmatched in performance and functionalities.

## DU6771

### SPECIFICATIONS

Image	<b>Display Type</b>	Single chip DLP® Technology by Texas Instruments
	<b>Brightness</b>	6500 ANSI Lumens
	<b>Native Resolution</b>	WUXGA (1920 x 1200)
	<b>Max. Supported Resolution</b>	WUXGA (1920 x 1200) @60Hz
	<b>Contrast Ratio</b>	3,000:1
	<b>Native Aspect Ratio</b>	16:10
	<b>Keystone Correction</b>	Vertical +/- 30°, Horizontal +/- 30°
Optical	<b>Throw Ratio</b>	8 optional lenses from 0.38:1 to 5.31-8.26:1 throw ratio range
	<b>Image Size (Diagonal)</b>	depending on lens selection
	<b>Projection Distance</b>	depending on lens selection
	<b>Projection Lens</b>	8 optional lenses from 0.38:1 to 5.31-8.26:1 throw ratio range
	<b>Zoom Ratio</b>	Motorized Zoom & Focus
	<b>Offset</b>	Motorized Lens Shift
	<b>Lens Shift Range</b>	Motorized Lens Shift
Features	<b>Features</b>	3D Mandatory Formats supported (top/bottom, right/left, frame sequential), Keypad lock
	<b>Video</b>	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Compatibility	<b>Video</b>	SDTV (480i, 576i) / EDTV (480p, 576p) / HDTV (720p, 1080i, 1080p), NTSC (M, 3.58/4.43 MHz), PAL (B,D,G,H,I,M,N) SECAM (B,D,G,K,K1,L)
Connectivity	<b>I/O Connection Ports</b>	VGA-In (15pin D-Sub), HDMI Number of Ports v.1.4a (2), DVI-D, Component (5 BNC) (RGBHV) , RJ45 (1: HDBaseT/LAN), RS-232, 3D-Sync (x2: In and Out), USB A (Power Only), USB B (Service), Remote Jack(wire remote)
General	<b>Lamp Life and Type</b>	4,500 / 5,000 Hours (Norma / Eco Mode), 300W x 2
	<b>Dimensions (W x D x H)</b>	510 x 470 x 210 mm
	<b>Weight</b>	18 kg
	<b>Noise Level</b>	35dB/30dB (Normal/Eco Mode)
	<b>Power</b>	Supply: AC 100-240V, 50/60Hz. Consumption: 572W (Eco Mode), 697W (Normal Mode), <0.5W (Standby)
	<b>Warranty</b>	Large Venue Warranty: 5 years projector / 1 year on lamp or 1.000 hours whichever comes first
	<b>Standard Accessories</b>	VGA Cable, User Manual (CD), Warranty Card (by region), Remote Controller (with battery), AC Power Cord, Remote Control Cable
	<b>Optional Accessories</b>	Spare Lamp P/N (3797865400-SVK), Remote Control P/N (5042221900)
	<b>UPC Code</b>	DU6771-BK: 813097022523 DU6771-WH: 813097022509

### OPTIONAL LENSES

Lens Name	Ultra Wide Zoom	Ultra Short Throw	Standard Lens	Wide Fix	Wide Zoom	Semi Long Zoom	Long Zoom 1	Long Zoom 2
<b>Aspect Ratio</b>	16:10	16:10	16:10	16:10	16:10	16:10	16:10	16:10
<b>Throw Ratio</b>	0.75-0.93:1	0.38:1	1.73-2.27:1	0.76:1	1.25-1.79:1	2.22-3.67:1	3.58-5.38:1	5.31-8.26:1
<b>Projection Distance</b>	0.62-10.36	0.85-2.74	1.45-24.85	0.64-8.50	1.05-19.59	1.87-40.33	3.01-59.02	4.42-91.54
<b>Image Size</b>	40-500	100-350	40-500	40-500	40-500	40-500	40-500	40-500
<b>Zoom</b>	1.25	1	1.3	1	1.41	1.65	1.5	1.55
<b>F Number</b>	1.96 - 2.3	2.0	1.7-1.9	1.85	1.85-2.5	1.86-2.48	1.85-2.41	1.85-2.48
<b>Focal Length</b>	11.3 - 14.1 mm	5.64 mm	26 - 34 mm	11.6 mm	18.7 - 26.5 mm	32.9 - 54.2 mm	52.8 - 79.1 mm	78.5 - 121.9 mm
<b>Part Number</b>	3797804200-SVK (D88-UWZ01)	3797866500-SVK (D88-UST01B)	3797744200-SVK (D88-ST001)	3797745100-SVK (D88-WF18501)	3797745200-SVK (D88-WZ01)	3797745000-SVK (D88-SMLZ01)	3797745400-SVK (D88-LOZ101)	3797744900-SVK (D88-LOZ201)